



Cool MF Series


The Cool MF series is designed to withstand up to 194°F (90°C) ambient temperature. Made for harsh, extreme heat environments such as die-cast facilities, foundries, iron forges, steel mills, power generation, factories, and chemical plants. Offering exceptional efficacy of 160lm/W and low maintenance cost to meet the demand of hot industrial environments. From 16,000 to 72,000 lumen output, it ideally replaces 250W-1000W HID fixtures.

Certifications and Ratings

UL1598 Wet Location
 UL 8750 LED Safety
 CSA C22.2 No. 250.13-14
 IP66/67
 IK09



Dimensions



Specifications

Power	100/150/200/300/450 W
Beam Angle	110°
Lumen Output	16,0000lm - 72,000lm
Driver Efficiency	≥ 90%
Voltage/Frequency	120/220/277V; 50/60hz
Power Factor	≥ 90% @120V
Surge Protection	6 KvA
Construction	Marine Grade Aluminum
Ambient Temperature	-40°F - 194°F (-40°C - 90°C)
DC Output Ripple & Noise	<200mVP-P
Lens Material	Tempered Glass
Hardware	Stainless Steel
Connection	3' cord
Mounting	Hanging/Yoke
Color Rendering Index	Ra>70
L70	20,000hrs@90°C, 30,000@80°C, 50,000hrs@70°C
Warranty	2/3/5 Year Fixture Warranty*

*Contact us for extended warranty information

Order Information

Cool MF Series


CMF	100	L	5K	T5	HR
Fixture	Wattage	Voltage	CCT	Optic	Mounting
CMF	100 - 16,000 lm 150 - 24,000 lm 200 - 32,000 lm 300 - 48,000 lm 450 - 72,000 lm	L - 120 M - 220 H - 277	5K Cool White	T5	HR - Hanging Ring HH - Hanging Hook JB - Junction box

Accessories

SC - Safety Cable

Photometrics

110°



1 (844) BLKNBLU

info@blackandbluelighting.com

1801 N. Memorial Dr, Racine, WI 53404 USA

www.blackandbluelighting.com

Black And Blue Lighting, LLC

B3
LIGHTING
TAKES A BEATING