



CANOPY™ Series

Hazardous Location Canopy Lighting

Canopy series canopy lights feature a square design, specifically crafted for petrol pumps and gas stations. They are certified for hazardous locations, meeting Class I, Division 2, Groups A, B, C, and D standards.

Compliance

NEC/CEC Standard

UL 844 Hazardous Locations

Class I Division 2, Groups A, B, C, D
Class I, Zone 2, Group IIC

CSA C22.2 No.137-18

UL 1598 Wet Locations

UL 8750 LED Safety

IP66/67 | IK07

Warranty

10-year limited system warranty

Lumen Maintenance: L70 > 150,000hours @ 25°C

Modular Design

2 models with light output ranging from 9,000 lumens up to 22,500 lumens.



60W / 75W



120W / 150W

Technical Data

Electrical

Rated Power	60W / 75W / 120W / 150W
Input Voltage	100-277, 347-480V/AC
Input Frequency	50/60Hz
Power Factor	> 0.9
Driver Efficiency	≥ 90%
DC output Ripple & Noise	< 200mVP-P

Optical

Lumen Output	9,000lm ~ 22,500lm
Luminous Efficacy (Lumens per Watt)	150 lm/W
Beam Angle	60° / 90° / 110°
Correlated Color Temperature (CCT)	2700K 3000K 4000K 5000K
CRI	Ra>70

Environmental

Ambient Operating Temperature -40°C~+50°C




Ambient Operating Humidity 10%~90% RH

Technical


Lens Material	Clear glass
Mounting Options	Pendant / Recessed / Hanging Ceiling / Surface
Net Weight	6kg (13.2 lbs) - 60W/75W 8.5kg (18.7 lbs) - 120W/150W

Dimensions

unit: mm(in)




Ordering Information and Mounting Accessories



Mounting Options



Thread



Accessories

